MALIBU COLONY COLLECTION

Nestled northwest of Los Angeles, Malibu is a 21-mile stretch of sand and surf with a star-studded celebrity history. This exclusive beach hideaway has been a refuge for Hollywood royalty since the Silver Screen era and remains a popular private enclave to date.

The Malibu Colony Collection reflects weathered modernism with a bold color palette drawn from the vibrant wildflowers along the coast, the glorious sunsets beneath the horizon, and the beautiful neutrals of the shoreline. The small-scale design of Carbon Beach™ mimics the feeling of the coastal sands and the soft surf of Little Dume, while the mid-scale Grotto Trail™ reinforces the idea of Malibu's steep clay slopes and windy trails over breathtaking coastline views.

BEILEY

LOS ANGELES



















MALIBU COLONY COLLECTION

GROTTO TRAIL™ **SPECIFICATIONS**

Style Number 4GT26 **Product Construction** Tufted Tip-Sheared

Fiber Antron® Legacy™ Type 6,6 Nylon

COLORCAST™ Dve Method Soil/Stain Protection XTERA™

Secondary Backing

High PerformancePC Broadloom

NexStep® Cushion Tile / AFIRMA™ Hardback Tile Carpet Tile

26 oz/yd² (881.5 g/m²) Yarn Weight Machine Gauge 1/12 in (47.2 ends/10 cm)

Pile Height

0.182 in (4.6 mm) High 0.142 in (3.6 mm) Medium Low 0.058 in (1.5 mm)

11.5/in (45.3 ends/10 cm) Stitches

7,719 oz/yd3 Pile Density

Total Weight

61 oz/yd2 (2,068.3 g/m2) High PerformancePC Broadloom NexStep® Cushion Tile 103 oz/yd² (3,492.3 g/m²) 84 oz/yd² (2,848.1 g/m²) AFIRMA™ Hardback Tile

Total Thickness

High PerformancePC Broadloom 0.275 in (7.0 mm) NexStep® Cushion Tile 0.375 in (9.5 mm) AFIRMA™ Hardback Tile 0.255 in (6.5 mm)

Pattern Repeat

Broadloom 24 in W x 36 in L (60.96 cm W x 91.44 cm L)

Carpet Tile

Passes Class 1, ≥ 0.45 W/cm² (ASTM-E648) Radiant Panel Smoke Density < 450 Dm corr (ASTM-E662), Flaming

Static ≤ 3.5 kV (AATCC-134), Step

Flammability Passes Methenamine Pill Test (CPSC-FF1-70) CARBON BEACH™

4CX26

Tufted Tip-Sheared

Antron® Legacy™ Type 6,6 Nylon

COLORCAST™ XTERA™

High PerformancePC

NexStep® Cushion Tile / AFIRMA™ Hardback Tile

26 oz/yd² (881.5 g/m²) 1/12 in (47.2 ends/10 cm)

0.182 in (4.6 mm) 0.142 in (3.6 mm) 0.058 in (1.5 mm)

11.7/in (46.1 ends/10 cm)

6,931 oz/yd3

61 oz/yd² (2,068.3 g/m²) 103 oz/yd2 (3,492.3 g/m2) 84 oz/yd² (2,848.1 g/m²)

0.265 in (6.7 mm) 0.365 in (9.3 mm) 0.245 in (6.2 mm)

36 in W x 72 in L (91.44 cm W x 182.88 cm L)

Passes Class 1, ≥ 0.45 W/cm² (ASTM-E648) < 450 Dm corr (ASTM-E662), Flaming

≤ 3.5 kV (AATCC-134), Step

Passes Methenamine Pill Test (CPSC-FF1-70)

When selecting colors beyond those swatched in the architect folder, COLORCAST™ utilizes a standard order size of 50 square yards in tile or broadloom (based on availability) and up to 5% overage, with no upcharges. For more information, please contact your local account executive.

STYLE NUMBERS

GROTTO TRAIL	CARBON BEACH	BACKING	SIZE
4GT260620R	4CX260620R	High PerformancePC Broadloom	12 ft (3.657 m) — Also available in Area Rugs
4GT260AA0T	4CX260AA0T	NexStep® Cushion Tile	18 in x 36 in (45.72 cm x 91.44 cm)
4GT260220T	4CX260220T	NexStep® Cushion Tile	24 in x 24 in (60.96 cm x 60.96 cm)
4GT260AA0K	4CX260AA0K	AFIRMA™ Hardback Tile	18 in x 36 in (45.72 cm x 91.44 cm)
4GT260220K	4CX260220K	AFIRMA™ Hardback Tile	24 in x 24 in (60.96 cm x 60.96 cm)








RECOMMENDED CARPET TILE INSTALLATION METHODS

18 in x 36 in

Ashlar



Herringbone













Bentley's High PerformancePC, NexStep® Cushion Tile, and AFIRMA™ Hardback Tile products are Cradle to Cradle Certified™ Silver. Bentley products are also certified under the NSF/ANSI Standard 140 - Sustainable Carpet Assessment (NSF 140). Six of Bentley's standard backing products are NSF 140 certified at the Gold level or above. Bentley's carpet products are manufactured in our California mill, a LEED for Existing Buildings: Operations and Maintenance (LEED®-EBOM) Gold certified facility. Please inquire about product warranties for specific backing options.

Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. Products that go through the shearing process may result in a small loss of yarn weight. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Carpet specifications and components are subject to normal manufacturing tolerances and may change without notice. Technical performance characteristics are subject to adjustment based on results of post-manufacture testing. Product warranted in accordance with the terms and conditions of Bentley's standard printed warranty in effect at time product is sold. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Made in USA. Warning: unauthorized reproduction of this carpet design constitutes copyright infringement. ©2017 Bentley Mills, Inc.





800.423.4709 | BENTLEYMILLS.COM