



**BENTLEY®**

OUTLIER





LEFT  
**OUTLIER™**  
80U230AA0T  
Habitat 801671  
18 in x 36 in  
HERRINGBONE

RIGHT  
**OUTLIER**  
80U2309A0T  
Extremity 801681  
Borderland 801682  
9 in x 36 in  
ASHLAR



LEFT

**OUTLIER**

8OU230AA0T

Environs 801677

18 in x 36 in

BRICK

RIGHT TOP

**OUTLIER**

8OU230220T

Subdivision 801678

24 in x 24 in

MONOLITHIC

RIGHT BOTTOM

**OUTLIER**

8OU230220T

Fringe 801679

24 in x 24 in

QUARTER TURN







LEFT  
**OUTLIER**  
80U230220T  
Borderland 801682  
24 in x 24 in  
BRICK

RIGHT  
**OUTLIER**  
80U2309A0T  
Environs 801677  
Fringe 801679  
9 in x 36 in  
HERRINGBONE



LEFT

**OUTLIER**

8OU230630R

Habitat 801671

12 ft 6 in

BROADLOOM

RIGHT

**OUTLIER**

8OU230AA0T

Habitat 801671

18 in x 36 in

ASHLAR





OUTLIER color line as featured in architect folder.



Frontier  
801670



Habitat  
801671



Verge  
801672



Territory  
801673



Brink  
801674



Margin  
801675



Vicinity  
801676



Environs  
801677



Subdivision  
801678




Fringe  
801679



Perimeter  
801680



Extremity  
801681




Borderland  
801682


The printed images may not be an accurate reproduction of the product's actual colorways. Please note that images were taken in a loft, full of natural light. We strive to offer an authentic representation, but images may vary according to press run and location lighting. These images are intended as a guide only. If you would like a sample of this product, please call Customer Care at 800.423.4709.

### RECOMMENDED CARPET TILE INSTALLATION METHODS


9 in x 36 in



Ashlar




Herringbone




Double  
Herringbone


18 in x 36 in




Ashlar



Brick




Herringbone




Monolithic


24 in x 24 in




Ashlar



Brick



Monolithic



Quarter Turn

Bentley's High PerformancePC, NexStep® Cushion Tile, and AFIRMA™ Hardback Tile products are Cradle to Cradle Certified™ Silver. Bentley products are also certified under the NSF/ANSI Standard 140 – Sustainable Carpet Assessment (NSF 140). Six of Bentley's standard backing products are NSF 140 certified at the Gold level or above. Bentley's carpet products are manufactured in our California mill, a LEED for Existing Buildings: Operations and Maintenance (LEED®-EBOM) Gold certified facility. Please inquire about product warranties for specific backing options.

Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. Products that go through the shearing process may result in a small loss of yarn weight. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Carpet specifications and components are subject to normal manufacturing tolerances and may change without notice. Technical performance characteristics are subject to adjustment based on results of post-manufacture testing. Product warranted in accordance with the terms and conditions of Bentley's standard printed warranty in effect at time product is sold. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Made in USA. Warning: unauthorized reproduction of this carpet design constitutes copyright infringement. ©2018 Bentley Mills, Inc.

# OUTLIER™

## SPECIFICATIONS

Style Number	8OU23
Product Construction	Tufted Textured Loop
Fiber	Antron® Lumena™ Type 6,6 Nylon
Dye Method	Solution Dyed
Soil/Stain Protection	XTERA™
Secondary Backing	
Broadloom	High PerformancePC
Carpet Tile	NexStep® Cushion Tile / AFIRMA™ Hardback Tile / AFFIXX™ Hardback Tile
Yarn Weight	23 oz/yd² (779.8 g/m²)
Machine Gauge	1/10 in (39.4 ends/10 cm)
Pile Height	
High	0.187 in (4.7 mm)
Medium	0.146 in (3.7 mm)
Low	0.090 in (2.3 mm)
Stitches	11.0/in (43.3 ends/10 cm)
Pile Density	7,582 oz/yd³
Total Weight	
High PerformancePC Broadloom	58 oz/yd² (1,966.5 g/m²)
NexStep® Cushion Tile	100 oz/yd² (3,390.6 g/m²)
AFIRMA™ Hardback Tile	81 oz/yd² (2,746.4 g/m²)
AFFIXX™ Hardback Tile	82 oz/yd² (2,780.3 g/m²)
Total Thickness	
High PerformancePC Broadloom	0.295 in (7.5 mm)
NexStep® Cushion Tile	0.360 in (9.1 mm)
AFIRMA™ Hardback Tile	0.275 in (7.0 mm)
AFFIXX™ Hardback Tile	0.280 in (7.1 mm)
Pattern Repeat	
Broadloom	Pattern Match Not Required
Carpet Tile	None
Radiant Panel	Passes Class 1, ≥ 0.45 W/cm² (ASTM-E648)
Smoke Density	< 450 Dm corr (ASTM-E662), Flaming
Static	≤ 3.5 kV (AATCC-134), Step
Flammability	Passes Methenamine Pill Test (CPSC-FF1-70)

## STYLE NUMBERS

OUTLIER	BACKING	SIZE
8OU230630R	High PerformancePC Broadloom	12 ft 6 in (3.810 m) — Also available in Area Rugs
8OU2309A0T	NexStep® Cushion Tile	9 in x 36 in (22.86 cm x 91.44 cm)
8OU230AA0T	NexStep® Cushion Tile	18 in x 36 in (45.72 cm x 91.44 cm)
8OU230220T	NexStep® Cushion Tile	24 in x 24 in (60.96 cm x 60.96 cm)
8OU2309A0K	AFIRMA™ Hardback Tile	9 in x 36 in (22.86 cm x 91.44 cm)
8OU230AA0K	AFIRMA™ Hardback Tile	18 in x 36 in (45.72 cm x 91.44 cm)
8OU230220K	AFIRMA™ Hardback Tile	24 in x 24 in (60.96 cm x 60.96 cm)
8OU2309A0X	AFFIXX™ Hardback Tile	9 in x 36 in (22.86 cm x 91.44 cm)
8OU230AA0X	AFFIXX™ Hardback Tile	18 in x 36 in (45.72 cm x 91.44 cm)
8OU230220X	AFFIXX™ Hardback Tile	24 in x 24 in (60.96 cm x 60.96 cm)

AFFIXX™ Hardback Tile is not CE Mark certified.

antron. 





800.423.4709 | BENTLEYMILLS.COM

14641 E. DON JULIAN ROAD, CITY OF INDUSTRY, CA 91746